



WALL





# CONRAD BRICK™

Inspired by Scandinavian simplicity, Conrad Brick™ exemplifies soft sophistication. The 2 x 8 glossy wall tile is available in a curated color group of soft and serene earth tones. This versatile shape can be installed in a standard straight-joint pattern, herringbone pattern, and more.

Cover photo features Conrad Brick™ Siren 2 x 8 on the island and back wall inset and Unglazed Mosaics™ Black and Ice White Penny Round Diamond Mosaic on the floor. Above photo features Conrad Brick™ Linen 2 x 8 on the backsplash and Historic Bridge Old Hollow 6 x 36 matte on the floor.



FINISHES: GLOSSY

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR

MATERIAL



PG  
GLAZED PORCELAIN

PRICING



LOW HIGH

SPECIAL FEATURES



STEPWISE™



TRUEEDGE™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

WALL

WALL TILE



POLAR CB90



LINEN CB91



TIN CB92



STARK CB93



SAGE CB94



SIREN CB95



MARINE CB96



WATERPROOF



STAINPROOF



DENTPROOF



FIRE-RESISTANT



CLIMATEPRO™



SIMPLICLEAN™

VISIT [AMERICANOLEAN.COM/WHYTILE](http://AMERICANOLEAN.COM/WHYTILE) FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

## FINISHES: GLOSSY

### USAGE



### MATERIAL



### PRICING



### SPECIAL FEATURES



NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

## WALL

### SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	2 x 8 Wall Tile	2" x 7-15/16" (5.08 cm x 20.26 cm)	3/8"	4.00	36

### APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [americanolean.com/DCOF](http://americanolean.com/DCOF).

#### APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

### INSTALLATION

Grout Joint Recommendation	Shade Variation
1/16"	 High (V3)

### PERFORMANCE CHARACTERISTICS

	ASTM#	RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs.
Scratch Hardness	MOHS	6.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: [americanolean.com/information/TestResults](http://americanolean.com/information/TestResults).

### NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

For additional information refer to "Factors to Consider" at: [americanolean.com/Factors](http://americanolean.com/Factors).

Use of a latex modified thin-set is recommended for installation.

For more information, visit [americanolean.com](http://americanolean.com).

### FEATURES



POST-CONSUMER  
RECYCLED MATERIALS



PRE-CONSUMER  
RECYCLED MATERIALS



REVEAL IMAGING®



All or select items within this series meet the requirements for these qualifications.  
For more information visit [americanolean.com](http://americanolean.com).

